



designed for scientists



VACSTAR lite Starter Plus Solution Vacuum pump

/// Data Sheet

The VACSTAR lite Starter Plus Solution package is a modern, user and environmentally friendly solution for your vacuum applications in the laboratory. By combining the VC 10 lite vacuum controller with the VACSTAR lite vacuum pump, the desired setpoint can be conveniently set manually via the large and easy-to-read TFT display. In addition, the program mode enables simple programming of several ramp steps to efficiently control complex simulations. The VSE 1 emission condenser prevents solvents from being released into the room air, thus protecting users and the environment.

This solution is perfect for a variety of classic laboratory applications, including separation, filtration and drying processes. Ideal for use in conjunction with rotary evaporators, reactors, tempering chambers, centrifuges and other



designed for scientists

laboratory equipment.

Advantages and technical features:

- Integrated device communication: the vacuum controller seamlessly synchronizes with circulators, resulting in optimized lab procedures and increased overall performance.
- Longer lifecycle: An integrated valve cleaning function removes solvent residues, extending system life and reducing maintenance.
- USB/RS232 interfaces: These allow connection to labworldsoft® laboratory software for advanced process control.
- Increased safety: The VSE 1 emission condenser ensures increased user safety by preventing solvent residues from entering the room air.

Technical Data

Final pressure without gas ballast [mbar]	9
Suction levels	2
Cylinder	2
Connection diameter suction side [mm]	8
Connection diameter pressure side [mm]	8
Input pressure [mbar]	10 - 1030
Two-point control	yes
Analog speed vacuum control	yes
Speed range [rpm]	285 - 1100
Speed (50Hz) [rpm]	1100
Speed (60Hz) [rpm]	1100
Nominal speed [rpm]	1100
Display	LED line
Pressure unit / scale	mbar
Vacuum speed control interface	VACSTAR
Noise at low. pressure [dB(A)]	54
Material in contact with medium	Al ₂ O ₃ ; PTFE; FFPM; PPS; NBR
Housing material	alu-cast coating / thermoplastic polymer
Dimensions (W x H x D) [mm]	115 x 292 x 280
Weight [kg]	8.5
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity	80% (up to 31°C), decreasing linearly to max. 50 (@40°C)
Protection class according to DIN EN 60529	IP 20
USB interface	yes
Analog input	yes
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	120
Power input standby [W]	5
Fuse	2x T4A 250V